

KIWO RED BLOCKOUT

(formerly KIWO 90009)

1. DESCRIPTION

KIWO RED BLOCKOUT is used for retouching and blocking-out solvent resistant stencils.

2. APPLICATION

For retouching pinholes and small defects KIWO RED BLOCKOUT with a fine brush.

For blocking out larger areas KIWO RED BLOCKOUT using a plastic or cardboard scraper or a coating trough.

3. DRYING

The filler dries smoothly within 10-30 minutes, depending on the applied thickness, drying conditions and the mesh count.

4. DECOATING / CLEANING

KIWO RED BLOCKOUT is not water resistant and tools can be cleaned with warm water. When decoating the screens rinse off the filler with water first or spray the reclaiming solution directly on the screens.

5. PHYSICAL DATA

Color:	red or blue
Consistency:	Viscous liquid
Shelflife:	1 year at 68 degrees Fahrenheit (20 degrees Celsius)
Flash point:	Not applicable
TLV:	Not applicable
VOC:	None
HMIS rating:	Health - 1 Flammability - 0 Reactivity - 0

6. PERSONAL PROTECTION

It is recommended to wear protective glasses and gloves. See Material Safety Data Sheet for additional information.

6. PACKAGING

1 quart, 1-gallon, 5-gallon, 55-drum containers

7. ENVIRONMENTAL PROTECTION

KIWO RED BLOCKOUT can be eliminated through biological decomposition in adapted waste water treatment plants. The working solution can generally be emptied into the drains. Consult local authorities for local regulations.

8. ADDITIONAL INFORMATION

For additional product information, please visit our web site at www.kiwo.com. For further information contact your KIWO distributor or KIWO direct.

Thank you for choosing **KIWO**.